


J38702



1- The 125mm diameter posts are made of painted galvanised steel. The grained finish has a slightly undulating surface for increased scratch resistance.




2- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.



3- The slatted fences are produced using post-consumer waste, mainly recycled food and drinks containers (polyethylene, aluminium). This environmental impact reducing material is an inert and robust compound which is hard-wearing, resistant to UV light and fluctuations in temperature, and able to retain its shape over time. It is also rot-proof, making it a reliable option for outdoor applications.



4- The platform and the steps are made from a 12.5mm thick textured and non-slip compact material (HPL).



5- The 60cm wide walkway is made of a beveled aluminum treadplate.



6- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.

Proludic



7- Injection moulded polyamide fixings connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.



8- The sliding surface is made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.



9- The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

