

Parcours (caractéristiques techniques)

J5400



1- The 125mm round posts are made of laminated timber, which have not been treated with chrome or arsenic. Splinter-free, the laminate provides great strength and dimensional stability. The posts are protected from wear and tear caused by fungi and insects.

The caps are made of injection moulded polyamide.



2- The platform floors are made from a 18mm thick, non-slip polyethylene material.



3- The 16mm diameter ropes are made of galvanised steel cable covered with polyester. The cables are linked together and held in place by injected polyamide spheres.



4- The net fittings are made of polyamide.

The fittings are composed of two distinct parts for ease of maintenance of individual strands.



5- **Injected aluminium elements** are fixed on the posts with self-drilling screws to provide links between the ropes and the posts.



6- Injection moulded polyamide fixings connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.





7- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.



8- The climbing holds are made of polypropylene. They are non-toxic, inflammable and shock and UV resistant. They give the units their strength and help to protect them from vandalism.



9- The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

